

WALL MOUNTED TALKBACK SPEAKER MODEL V-1061-BK, V-1061-W

FEATURES:

UTILIZES STANDARD CAT 3, 5, OR 6 CABLE

USED WITH TALKBACK PAGE CONTROLS

ELECTRICALLY, ACOUSTICALLY MATCHED PARTS



DESCRIPTION:

Wall surface mounted speaker assembly complete with 45 ohm speaker, sloped baffle and mounting bracket.

SPEAKER ELEMENT

Cone Diameter: 8.0" (20.32 cm) Voice Coil
Impedance: 45 ohm

INPUT

Impedance: 45 ohms nominal
Rated Power: 12 Watts

FREQUENCY RESPONSE

80 Hz to 12 kHz

SPEAKER POWER RATING

12 Watts

ENVIRONMENT

TEMPERATURE: -4 TO +131 °F (-20 to +55 °C)
HUMIDITY: 0-95% Non-Condensing

HOUSING AND FINISH

The baffle is constructed of .5" (1.27 cm) particle board covered with a simulated black or white vinyl with matching grille cloth.

DIMENSIONS AND WEIGHT

9.6" (24.38 CM) H X 11.5" (29.21 cm) W X 4.2"
(10.67 cm) D
WEIGHT: 4.5 lbs (2.04 kg)

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS
MODEL V-1061-BK, V-1061-W
WALL MOUNTED TALKBACK SPEAKER

The Wall Speaker, Model V-1061A shall consist of a 45 ohm speaker and sloped baffle.

The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 60 Hz to 12 kHz. The speaker element shall be cone type with 5 oz (142 g) ceramic magnet. Diameter of speaker cone shall be 8.0" (20.32 cm) with 2.0" (5.08 cm) whizzer cone. Voice coil impedance shall be 45 ohm. Speakers utilizing an 8 ohm voice coil are not acceptable. Operating temperature shall be -4 to + 131 °F (20 to + 55 °C).

The baffle shall be constructed of .5" (1.27 cm) particle board covered with simulated black or white vinyl and have a matching grille cloth.

Maximum dimensions of the housing shall be 9.6" (24.38 cm) H x 11.5" (29.21 cm) W x 4.2" (10.67 cm) D. Shipping weight is 4.5 lbs (2.04 kg).

Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened.
(A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs
(major repairs will be subject to additional charges for parts and labor).

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.